

substitute therefor --10 provided with the cams 3 and

B3 ~~bearing rings 6~~--.

Page 6, line 14, please delete "to be disposed on the pipe, are".

N/E Page 6, line 14, after "cams" please insert --10 and the bearing rings 6--.

#### IN THE CLAIMS

1. (twice amended) A built-up camshaft comprising a pipe [or a solid rod,] coated by a jointing coating on an outer cylindrical surface and an inner cylindrical surface and having an outer pipe diameter and an inner pipe diameter and having cam places, bearing ring places and pipe end places;

B4 cams [,] formed as rings with an outer cylindrical flange and an inner cylindrical flange and provided with the jointing coating on an inner cylindrical surface of the inner cylindrical flange and having a cam opening diameter slightly smaller than the outer pipe diameter and positioned at the cam places and bearing rings [, end pieces , and other parts, wherein the cams (3), the end pieces (6), the bearing rings, and the other parts are connected by means of longitudinal compression joints to the pipe or to the solid rod, wherein the parts to be connected are and] provided

with [a suitable surface] the jointing coating on inner surfaces being in contact with the pipe and having an inner ring diameter slightly smaller than the outer pipe diameter and positioned at the bearing ring places and end pieces provided with the jointing coating on outer cylindrical surfaces and having an outer end pieces diameter bigger than the inner pipe diameter, wherein the jointing coating of the pipe and the jointing coating of the cams, the bearing rings and the end pieces create durable joints between the pipe and the cams, the bearing rings and the end pieces and wherein the surface coating prevents a tribocorrosion and increases [the] load capacity as compared to conventional compression joints.

2. (amended) The built-up camshaft according to claim 1, wherein the jointing coating [(2, 5)] is a joint-stable conversion coating.

3. (amended) The built-up camshaft according to claim 1, wherein the jointing coating [(2, 5)] is [a metal coating or] a cement coating.

4. (amended) The built-up camshaft according to claim

G3  
cont  
B4  
cont  
1, wherein at least one of the pipe [or the solid rod and/or], the cams, the end pieces, the bearing rings [, and the other parts] are made out of one of the group of metal, ceramics, plastics [or other materials,] by one of cutting [or], non-cutting, [by] milling, [or] forging in at least one of massive [or] and profiled form.

5. (amended) The built-up camshaft according to claim 1, wherein the outer [jacket face] cylindrical surface and the inner cylindrical surface of the pipe [or of the solid rod has a drawn quality or] is [completely or] at least partially mechanically machined.

B5  
D2  
6. (new) A built-up camshaft comprising a pipe coated with a crystalline phosphate coating on an outer cylindrical surface and on an inner cylindrical surface and having an outer pipe diameter and an inner pipe diameter;

cams and bearing rings having an inner diameter smaller than the outer pipe diameter and end pieces having an outer diameter bigger than the inner pipe diameter and connected by means of compression joints to the pipe and provided with the crystalline phosphate coating on surfaces being in

contact with the pipe, wherein the crystalline phosphate coating prevents a tribocorrosion and increases load capacity as compared to conventional compression joints and creates stable joints between the pipe and the cams, the bearing rings and the end pieces.

B3  
cont

7. (new) A built-up camshaft comprising a pipe coated by a cement on an outer cylindrical surface and an inner cylindrical surface and having an outer pipe diameter and an inner pipe diameter; cams and bearing rings having an inner diameter smaller than the outer pipe diameter and end pieces having an outer diameter bigger than the inner pipe diameter and connected by means of compression joints to the pipe and provided with the cement on surfaces being in contact with the pipe, wherein the cement prevents a tribocorrosion and increases load capacity as compared to conventional compression joints.

G3  
cont

8. (new) A method for building a camshaft comprising making a pipe having an outer pipe diameter and an inner pipe diameter; coating the pipe with a jointing coating on an outer

63 cont  
B5 cont  
cylindrical surface and on an inner cylindrical surface;  
making cams in form of rings with an outer cylindrical  
flange and an inner cylindrical flange and having a cam  
opening diameter smaller than the outer pipe diameter;  
coating cams with the jointing coating on surfaces to be  
placed in contact with the pipe;  
making bearing rings having an inner bearing ring diameter  
smaller than the outer pipe diameter;  
coating the bearing rings with the jointing coating on  
surfaces to be placed in contact with the pipe;  
making end pieces having an outer end piece diameter smaller  
than the inner pipe diameter;  
coating the end pieces with the jointing coating on surfaces  
to be placed in contact with the pipe;  
connecting the cams, the bearing rings, and the end pieces  
by means of compression joints to the pipe;  
and allowing the jointing coating to create stable joints  
between the pipe and the cams, the bearing rings and the end  
pieces by hardening the jointing coating.

#### REMARKS

Claims 1 through 5 continue to be in the case.  
Claims 1 through 5 and are being amended. New claims 6  
through 8 are being introduced.